

Comparative Measurements of Atmospheric Transparency at  
350  $\mu\text{m}$  Wavelength

Simon J. E. Radford\*  
National Radio Astronomy Observatory  
949 N. Cherry Ave.  
Tucson, AZ 85721-0655  
email: sradford@nrao.edu

Abstract Submission Form  
1998 National Radio Science  
Meeting

*Reference #* 0000  
*Session* 0.00

Comparative measurements of atmospheric transparency are underway at three current or proposed sites for submillimeter wavelength astronomy: the South Pole (2835 m), Mauna Kea (CSO, 4070 m), and Chajnantor, Chile (5000 m). Identical broadband tipping photometers determine the atmospheric transparency at each site about four times per hour by measuring the increase in sky brightness with zenith angle. The instruments, based on ambient temperature pyroelectric detectors, have resonant metal mesh filters defining a 105 GHz passband (FWHM) matched to the 350  $\mu\text{m}$  atmospheric window. Two internal loads at different temperatures are used to calibrate the detector response. Data from Mauna Kea are being cross calibrated against data from a 225 GHz tipping radiometer, from 808–846 GHz heterodyne measurements (CSO), from 350  $\mu\text{m}$  broadband (SCUBA on JCMT) measurements, and from broadband spectroscopy (FTS on CSO). Data from Chajnantor are being cross calibrated against data from a 225 GHz tipping radiometer and from a broadband spectrometer (FTS). Data from both Chajnantor and the South Pole will be compared to radiosonde data.

Measurement of the atmospheric transparency in the 350  $\mu\text{m}$  window directly assesses site quality for broadband astronomy. The relative shapes of the filter bandpass and the atmospheric window might, however, vary with site conditions, as might the relationship between the measured broadband transparency and the narrowband transparency at any particular frequency in the window. These effects were gauged with atmospheric models. Both effects show little or no dependence on site conditions or on model details. Hence broadband transparency measurements are good indicators of narrowband transparency. Sites may be compared on the basis of the measured broadband transparency without recourse to models of how the transparency depends on atmospheric water vapor, temperature, and pressure.

Cumulative distributions of the measured zenith transparency at the three sites will be discussed as well as seasonal and diurnal variations.

The NRAO is a facility of the National Science Foundation operated under cooperative agreement by Associated Universities, Inc.

1. (a) Simon Radford  
NRAO  
949 N. Cherry Avenue  
Tucson, AZ 85721-0665 USA  
sradford@nrao.edu
- (b) 520-882-8250
- (c) 520-882-7955
2. J
3. (a) Atmospheric transmission  
at mm/submm  
wavelengths
4. I, Program chair: Simon  
Radford
5. No special instructions

Date received: 23 May 95  
Formatted: September 11, 1998  
Form version: 1.0